



## List No. WNM1770

NH / NM / NMX

15 Way High Integrity Consumer Unit 100A Main Switch, 80A 30mA RCDs, Flexible Configuration with 10 MCBs



- 15 Way Flexible configuration as Dual RCD or High Integrity, space for RCBOs. NM Range.
- 100A Twin terminal Main Isolator
- 80A 30mA Type A RCDs
- Curved Visor with temporary locking facility
- Populated with 10 Type B Miniature Circuit Breakers (3x6A, 2x16A, 5x32A) and 5 blanks

### Product Specification Data

Revision Date: 15/10/2021

|  |  |
|--|--|
| Mounting method                        | Surface mounted (plaster)                  |
| Number of phases                       | 1  |
| Protection                             | Miniature- / earth leakage circuit breaker |
| Total number of groups                 | 3  |
| Number of poles main switch            | 2  |
| Main switch rated current              | 100 A                                      |
| Over voltage protection                | No   |
| Material housing                       | Steel                                      |
| Degree of protection (IP)              | IP2XC                                      |
| Height                                 | 261 mm                                     |
| Width                                  | 438 mm                                     |
| Width in number of modular spacings    | 21   |
| Depth                                  | 121 mm                                     |
| Extension possible                     | No   |
| With transparent cover                 | No   |
| Lockable                               | Yes  |
| Product Standard/s                     | BS EN 61439-3                              |
| Frequency                              | 50 Hz                                      |
| CE Conformity                          | Yes  |
| WEEE Symbol                            | Yes  |
| UKCA Conformity                        | Yes  |
| Amperage                               | 100 A                                      |
| Operating Voltage                      | 230 V                                      |
| Type of Current                        | AC   |
| Consumer Unit Type                     | High integrity                             |
| Total final circuit modular ways       | 15   |
| Busbar type                            | Flexible                                   |
| Main switch rating                     | 100 A                                      |
| Main switch final circuit modular ways | Flexible                                   |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electricum website.

|                                  |                 |
|----------------------------------|-----------------|
| RCD 1                            | 80A 30mA type A |
| RCD 1 final circuit modular ways | Flexible        |
| RCD 2                            | 80A 30mA type A |
| RCD 2 final circuit modular ways | Flexible        |
| Colour RAL                       | 9010            |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited**, Walkmill Lane, Cannock WS11 0XE  
01543 455000 [www.electrium.co.uk](http://www.electrium.co.uk) [info@electrium.co.uk](mailto:info@electrium.co.uk)